

MATERIAL SAFETY DATA SHEET

FLEXIBLE VINYL EXTRUSIONS

The data presented here applies to all **Loxcreen** Flexible PVC Extrusions. Although extrusions vary in terms of physical properties or other characteristics, safety and handling precautions are similar for all.

SECTION I: PRODUCT IDENTIFICATION

Manufacturer's Name: Loxcreen Flooring Group

Address: 5720 Ambler Dr., Mississauga, ON, CANADA, L4W 2B1

Phone: 905-629-4875

SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Family: PVC Compounds

CAS Registry Number: N/A

Alloying Elements: CAS Number

PVC Homopolymer 9002-86-2 Organo-Barium-Zinc 8052-41-3 Di-sec-octyl Phthlate 117-81-7 Limestone Dust 1317-65-3 Quartz 14808-60-7

SECTION III: PHYSICAL DATA

Materials At Normal Conditions: Solid

Appearance And Odor: Odourless extruded solid

Acidity Alkalinity: N/A Vapor Pressure: N/A

Melting Point: 221 – 410 °F (degrees Fahrenheit)

Specific Gravity: 1.17 to 1.75 $[H_2O = 1]$

Boiling Point: N/A

Solubility In Water (% by weight): Slight/Negligible (Considered Insoluble)

SECTION IV: PREVENTATIVE MEASURES

Precautions For Handling & Storage:

Handle and use under well ventilated conditions. Do not store or consume food in processing areas, and wash hands prior to eating, smoking or using

personal hygiene facilities.

Precautions for Maintenance & Repair of Contaminated Equipment:

N/A



SECTION IV: PREVENTATIVE MEASURES (CONT'D)

Other: Cool regrind before placing in containers to prevent decomposition. Under

abnormal conditions (equipment malfunctioning, etc.), decomposition may occur resulting in fumes which will contain the combined vapors and odors from all ingredients. Use HIOSH-approved respirators when removing

decomposed material.

Eye Protection: Use of safety glasses is recommended during processing.

Protective Glove: Rubber, worn when cleaning condensate from exhaust hood/other surfaces.

SECTION V: TOXICOLOGICAL PROPERTIES

Inhalation: Excessive processing vapors may produce acute health effects in some

individuals with bronchial asthma and other types of chronic respiratory

diseases. Bronchial spasm may develop if exposure is prolonged.

Ingestion: Not likely

Skin: May cause irritation

Eyes: Not likely

SECTION VI: FIRST AID MEASURES

For Skin Contact: Remove particles by thoroughly washing with soap and water.

For Inhalation: If irritation from exposure to process fumes persists, remove affected

individual(s) and call a physician.

SECTION VII: FIRE AND EXPLOSION DATA

Flash Point: N/A

Auto Ignition Temperature: N/A

Extinguishing Media Extinguish as if an ordinary combustible (NFPA Class A material) using water

(which is most effective), or ABS dry chemical, or AFFF or protein foam.

Special Fire Fighting Procedures: Positive pressure self-contained breathing apparatus (SCBA) is suggested

during and immediately after a fire.

Unusual Fire & Explosion Hazard: Thermal decomposition liberates hydrogen chloride in addition to typical

combustion gases such as carbon monoxide.



SECTION VIII: REACTIVITY

Stability: Stable

Incompatibility: N/A

Conditions To Avoid: N/A

SECTION IX: ENVIRONMENTAL

Spill Or Leak Procedures: Vacuum or sweep into a closed container for reuse or disposal. Dispose of or

incinerate in accordance with local regulations.

Waste Disposal Methods: Dispose of or incinerate in accordance with local regulations at a

licensed/permitted facility. Incineration may yield hydrogen chloride gas.

SECTION X: ADDITIONAL INFORMATION

Note: PVC Homopolymer has less than 0.1% v.c. & is not considered a hazardous

chemical based on supplier data. It is listed here because melting could possibly liberate v.c. in excess of above v.c. limits. Di-sec-octyl Phthalate is

listed as an IARC carcinogen.

SECTION XI: PREPARATION INFORMATION

MSDS Prepared By: Loxcreen Flooring Group

Phone Number: 1 - 800 - 265 - 2977

Date: August 4, 2009

While Loxcreen Flooring Group, believes that the data contained herein is accurate and derived from qualified sources, the data is not to be taken as a warranty or representation for which Loxcreen Flooring Group assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State and local laws and regulations.